

# Farm Pro

Simply The Best

## 2.2m & 3.2m<sup>3</sup> Uni Bin

### Features (Std)

- Remote and Manual Auger Control
- Galvanised Cone & Stainless Steel Slide Opening
- Hot Dipped Galvanised Chassis
- Hot Dip Galvanised 6" Auger. "PVC Lined" (Std)
- Double Flight Auger Pickup
- Gas Strut Raise Assist On Auger
- 1 Meter Drop Tube
- Swing Up H/Duty Jockey Wheel



**1.8 m<sup>3</sup> Uni Bin "Elec Start Upgrade"**  
**Special Production (Fit Under Super Bin)**



### 2.2m<sup>3</sup> Uni Bin Tandem

- **6.5hp** 4 Stroke Motor on 2.2m<sup>3</sup> & **9hp** 4 Stroke Motor on 3.2m<sup>3</sup> Unit
- 3.2m<sup>3</sup> Standard with Disc Brakes & Off Road Wheels
- Variable Flow Control On Bin Opening
- Augers Grains / Fertilisers to Ground or Top Auger Discharge



- 43 Degree Cone Angle on all Units "TOTAL CLEAN OUT"
- 15 hp "T" Gear Box With Chain Drive to Auger
- Concealed Wiring
- LED Power Indicator Light and Circuit Breaker
- 4 Year Structural Warranty

**Australian Designed, Manufactured & Supported**

[www.farmpro.com.au](http://www.farmpro.com.au)

[info@farmpro.com.au](mailto:info@farmpro.com.au)

Ph 03 5495 3101, 20 Kell Rd, St Arnaud, Vic, 3478

# Farm Pro

## Simply The Best Options

- Optional Extra Length Augers Available from .100 to 2.400m Folding
- Multiple Auger Discharge Selection
- Top & Ground Side Discharge Outlet
- Override Disk (Std 3.2) or Electric Brakes
- 12 Volt Electric Ram With Wireless Remote
- 9.0/13 hp Motor Electric Start Upgrades
- Battery & Electrics with LED's
- 2 Pac Epoxy Coated Bin For Fertilisers
- Additive Box (Suits Powder or Granuals)
- Weather Protection Cap

## Specifications

### 2.2m<sup>3</sup> Uni Bin

Overall Length:	3.400m
Overall Width:	1.650m
Overall Height:	1.830m
Overall Weight:	440kg
Bin Length & Width:	1.500m
Motor Size:	6.5hp
Wheels / Tyres:	205/65 R16
Tow Coupling:	50mm Ball - 2.000kg
Lift Auger:	HDG 6"

### 3.2m<sup>3</sup> Uni Bin

Overall Length:	3.400m
Overall Width:	1.650m
Overall Height:	1.830m
Overall Weight:	650kg
Bin Length & Width:	1.500m
Motor Size:	9.0hp
Wheels / Tyres:	245/70 R16
Tow Coupling:	50mm Ball - 2.000kg
Lift Auger:	HDG 6"
Tarp:	Full Length/Width Rope Track & Cord

### 1.5m Auger: (Std)

Distance From Unit to Auger Tip:	.800m
Height Underneath Outlet:	2.200m

### 2.4m Auger: (Option)

Distance From Unit to Auger Tip:	1.600m
Height Underneath Outlet:	3.300m



**Electric Start Motor**



**Battery Electrics**



**Additive Box**



**Feeder Filling**



**Weather Proof Electronics**



**Heavy Duty Tarp**



**Roll Top Tarp**



**15hp Gear Box**



**Electric Ram**



**Manual Shute Control**



**Centered Auger Flight**

[www.farmpro.com.au](http://www.farmpro.com.au)

[info@farmpro.com.au](mailto:info@farmpro.com.au)

[03 5495 3101](tel:0354953101)

\*\*Options and Specifications subject to change due to constant product improvement\*\*