

Multi Bin 4.4m³



2.2m³ twin bins (4.4m³ total)

14hp electric start motor

Wireless remote (start/stop) auger control

Wireless linear actuators for each bin

Epoxy coated front bin fit for fertiliser

Electric brakes both axles and breakaway

Gas strut auger lift

Telescopic drop tube

Steel engine cover & weather protection cap

15hp "T" gear box & direct coupled electromagnetic clutch

12V LED lights

Chequer plate side steps, walkway & grab handles

Heavy duty jack stand

Mix grains through cross auger to ground or top auger discharge

Auger out-rate average 290kg p/m (*urea)*

Product Capacity (per bin)

Wheat - 1800kg	MAP - 2090kg
Barley - 1390kg	Granulated urea - 1690kg
Oats - 1290kg	Single super - 2310kg

All weights are approximate + 5% compaction

Specifications

Overall length: 4700mm

Overall width: 1940mm

Overall height: 2250mm

Overall weight: 980kg *approx.*

Bin fill height (side of bin): 2100mm

Motor size: Kohler CH440 (14hp) 18a charge

Wheels/Tyres: White Sunraysia 31x10.5 R15

Tow coupling: 3500kg (50mm)

Cross and lift auger: Hot dip galvanised 6" welded auger tube *PVC lined*

Tarp: Roll top (full length and width)

2.8m auger (Std) PVC lined:

Distance from wheel to auger tip: 1675mm-3125mm

Height underneath green poly outlet: 3650mm

1.5m auger (Option):

Distance from wheel to auger tip: 875mm

Height underneath green poly outlet: 2550mm

4 year structural warranty



Options

- Elecbrakes wireless brake controller
- Linear actuator position/timer controls
- Dual side discharge outlets
- Multiple auger selection (up to 1.5m)
- Automatic, adjustable additive box (suits powder, granules, pellets)
- Scales (Rinstrum R320 indicator) [5t load cells] - Bluetooth available



*AS WE CONSTANTLY STRIVE TO CREATE THE BEST PRODUCTS. OPTIONS AND SPECIFICATIONS ARE SUBJECT TO CHANGE.