

Opti Bin 1.3m³ - 6.4m³

Single or Tandem Axle



Galvanised steel cone and hot dip galvanised chassis and frame

Jockey wheel or jack stand on all models

45° cone angle on 2.2 & 4.4m³ units

Galvanised mudguards on all units

39mm round dura flex axle on 1.3m³ units, 40mm square on 2.2m³ units, 50mm square/round on 6.4m³ units, and 45mm on all other units



All tandem units have LED lights and wiring

Easy to clean and wash out - all galvanised

Australian Designed, Manufactured & Supported

- Easily upgrade to remote control electric rams
- Adjustable and serviceable control systems
- 16" 5-stud Ford off road tyres or 15" 5-stud Ford Sunraysia highway tyres
- 1.3m³ units can be conveniently towed by an ATV or UTV (subject to manufacture specifications)
- 4.4m³ unit has standard 2 x 2.2m³ compartments to make feeding large mobs or **mixing grains simple**

Specifications

Single Bin, Single Axle

Cone Sizes: 1.5m W x 1.5m L x 1.6m

Chassis: 75 x 50 mm RHS

Overall Length (including tow pull): 3.200m

Overall Height (Side)

1.3 Unit: 1.200m

2.2 Unit: 1.750m

Overall Width (Mudguards):

1.3 Unit: 1.670m

2.2 Unit: 1.860m

Weight:

1.3 Unit: 230kg

2.2 Unit: 260kg

Wheels & Tyres:

15" Ford, S/H Highway (1.3m³)

16" Ford, S/H Off Road (2.2m³)

Single Bin, Tandem Axle

Cone Sizes: 1.5m W x 1.5m L x 1.6m

Cone Sizes: 1.8m W x 1.8m L x

1.6mm

Chassis: 100 x 50 mm RHS

Overall Length (including tow pull):

2.2 & 3.2 Units: 3.400m

Overall Height (Side)

2.2 Unit: 1.750m 3.2 Unit: 1.730m

Overall Width (Mudguards):

2.2 Unit: 1.860m 3.2 Unit: 1.890m

Weight

2.2 Unit: 360kg 3.2 Unit: 626kg

Wheels & Tyres:

15" Ford, S/H Highway (2.2m³)

16" Ford, S/H Off Road (3.2m³)

Twin Bin,

Tandem Axle

Cone Sizes:

1.5m W x 1.5m L x 1.6m

Chassis: 150 x 50 mm RHS

Overall Length (including tow pull):

4.600m

Overall Height (Side):

1.950m

Overall Width (Mudguards):

1.890m

Weight: 710kg

Wheels & Tyres:

16" Ford, S/H Off Road

Options

- Divider can be fitted to 2.2m³ units and above to use two feeds
- Bungi cord poly, heavy duty, or roll-top tarp or metal cover available for most units
- 12V wireless remote control electric ram open and close (multi position)
- Electric LED lights and wiring (standard on tandem wheel units)
- Override disk brake (standard on 3.2m³ and 4.4m³ units)
- Electric brakes
- Position/timer control

