

Paddock Roller *Silver Series*



Anti-catch frame (smooth outer frame) allows the Paddock Roller to slide past posts and fences

Cylinder can be water filled

Compacts hard clods or stones for better harvesting conditions

Can easily be upgraded to a dual or triple paddock roller

Heavy-duty removable draw bar [8-bolt connection] for sharper turns

Can be concrete filled for heavy duty work

Australian Designed, Manufactured & Supported

- Towing only requires low horse power
- 22.5" semi-trailer tyres for better and easier rolling (they don't bend like car tyres over clods and rocks)
- Hot dip galvanised bolted compression plates for quick and easy tyre replacement
- Fully hot dip galvanised frame & barrel
- RHS and 3mm plate barrel construction
- Greaseable long-life industrial roller bearings

Specifications

Tyre diameter: 41" / 1.05m

Standard roller weight: 330kg p/m (dry weight)

Water filling kg/m: 125kg

Concrete roller weight: 665kg p/m

Main frame size: 75mm RHS

Draw bar length: up to 4.3m

Tyre to pin: 3.3m

Silver Series roller widths:

2.7, 3.0, 3.3, 3.6, 4.0, 4.3, 4.5, 4.9, 5.2, 5.4 & 6.2m



Options

- Hydraulic off-settable draw bar
- Rear tow pull (rear frame is required for this option)
- Adjustable mud scraper bar (rear frame is required for this option)



*AS WE CONSTANTLY STRIVE TO CREATE THE BEST PRODUCTS, OPTIONS AND SPECIFICATIONS ARE SUBJECT TO CHANGE.