

Uni Bin 2.2m³ & 3.2m³



Remote and manual auger control

Galvanised cone & stainless steel slide opening

Hot dip galvanised chassis

Hot dip galvanised 6" auger "PVC lined" (Std)

Double flight auger pickup

Gas strut raise assist on auger

1 meter drop tube or galvanised chute

Swing up heavy duty jockey wheel

43 degree cone angle on all units

15hp "T" gear box with chain drive to auger

Concealed wiring

LED power indicator light and circuit breaker

4 year structural warranty

- 6.5hp 4 Stroke motor on 2.2m³ & 9hp 4 Stroke motor on 3.2m³ unit
- 3.2m³ standard with disc brakes & off road wheels
- Variable flow control on bin opening
- Augers grains / fertilisers to ground or top auger discharge

Specifications

2.2m³ Uni Bin

Overall length: 3.4m
Overall width: 1.65m
Overall height: 1.83m
Overall weight: 440kg
Bin length & width: 1.5m
Motor size: 6.5hp
Wheels/Tyres: 205/65 R16
Tow coupling: 50mm ball 2000kg
Lift auger: HDG 6"

3.2m³ Uni Bin

Overall length: 3.4m
Overall width: 2.1m
Overall height: 1.83m
Overall weight: 650kg
Bin length & width: 1.5m
Motor size: 9.0hp
Wheels/Tyres: 245/70 R16
Tow coupling: 50mm ball 2000kg
Lift auger: HDG 6"
Tarp: Full length/width rope track & cord

1.5m Auger: (Std)

Distance From Unit to Auger Tip: 0.8m **Height Underneath Outlet:** 2.2m

2.4m Auger: (Option)

Distance From Unit to Auger Tip: 1.6m **Height Underneath Outlet:** 3.3m

Options

- Extra length augers available from 100mm to 2400mm folding
- Multiple auger discharge selection
- Top & ground side discharge outlet
- Override disk (Std 3.2m³) or electric brakes
- 12V electric Ram with wireless remote
- 9.0/13 hp motor electric start
- Battery & electrics with LED's
- 2 Pac epoxy coated bin for fertilisers
- Additive box (suits powder or granules)
- Weather protection cap

